

IOP-PERFOS Fittings for putting in automatic

watering and / or lighting systems.

Simply on request, we can adapt the containers to suit your requirements: perforations, cut-outs, waterproof risers, etc.

Contact us when you place your order.

IOP-PERFOS: € 10 - 30 Excl tax/ Planter depending on complexity




IOP-SH IOP-SH40 IOP-SH60

Horticultural system.

Drainage system offering a water reservoir. IOP-SH: 5L/m² reservoir, EPS panel, 40mm thick. IOP-SH40: 8,7L/m² or 16L/m² reservoir according to the installation direction, recycled PEHD panel, 40mm thick. IOP-SH60: 6cm of reservoir, approx. 23L/m² when full of agregats, recycled PEHD panel, 60mm thick.

IOP-SH & IOP-SH40 replace the drainage section made of clay pellets / pozzolana. Cover with geotextile before adding substrate. IOP-SH60 as to be full of clay pellets (approx. 45L/m²). It can be used with a water level indicator IOP-INE.

acc. to capacity and format: from € 20 excl. tax/planter



IOP-INE

40 /50 /60 /70 /80 /90 /100 Water level indicator. For pots used indoors which have a watertight base. The float indicates the water level at the

base. The float indicates the water level at the bottom of the container. It allows the monitoring of watering.

Suitable for Indoor plant containers which have a watertight base. Price varies according to the height of the container.

€ 25 – 43 Excl. tax / container acc. to height of container



IOP-RL 50 / 65 / 100FC 75FR / 80FR ...

Installation on casters for handling.


Concealed under the container, the casters are not visible. They allow the plant container to be moved from time to time. As they are concealed, the casters cannot be fitted with brakes. If needed, provide a brake by retractable foot in option: «IOP-PFE» - or ask for visible castors with brakes.

May only be used on a flat, smooth and firm surface.

Beware of the risk of instability on <40cm width containers. Check the compatibility with the intended use; contact us.

€ 110 – 170 Excl. tax / container acc. to size

With brakes IOP-PFE: + \in 80 – 100 Excl. tax /container acc. to size



IOP-PLOT

28-40 / 40-55 / 85-140 ... Installation on adjustable PVC pedestals.

For a well-balanced installation, with a uniformly distributed load. Allows water to flow underneath the container, a good ventilation and also allows adjustments in the alignment of linear arrangements of containers.

For installation on sloping ground.

Suitable for > 40 cm wide containers. Suggested ranges of adjustment: 12/15/or 55 mm. Others on request.


€ 55 – 65 Excl. tax / container acc. to std ranges, others on request 6 PLOTS from €90 excl. tax/container

IOP-PR

Installation on adjustable feet.

Replaces IOP-PLOT for < 40 cm wide planters.

€ 120 – 140 Excl. tax /container acc. to size & slope



IOP-CLS

Lowered lateral partition(s)

Ideal for forming linears with a uniform mulching surface.

To adjust the alignment of the planters, add the IOP-PLOT option.

Before filling, plan to lay a geotextile felt straddling the two bins at the level of the lowered partitions.

€ 40 Excl. tax / container













IOP-PSX	Installation on extruded polystyrene panel	Installation on polystyrene weight distribution buffer. Avoids perforation if installing directly on waterproofing.	Check the admissible load per m².	€ 30 - 80 Excl. tax/per container acc. to size of container
IOP-MTP	Handling by forklift	Removable trap door concealing an access underneath the container for handling by forklift. Ideal for moving large containers from time to time.	Handle with care! The loaded container is subject to great stresses when being moved.	€ 160 Excl. tax/per container
IOP-ISOL	Wall insulation (PSX)	Fibre-cement already has a low thermal exchange coefficient. However, in areas with extremes of climate, wall insulation can be added.	Wall insulation only slows down the variations in temperature in the clump of soil. Provide protection for your plantation.	€ 40 - 90 Excl. tax/per container acc. to size of container
IOP-TES	Hole and crosspiece for secure fixing	Allows the passage and fixing of a previously ground-secured, threaded rod at the base of the container.	The tightening process must be carried out with care to avoid the risk of damaging the container.	€ 30 - 50 Excl .tax/per container
IOP-TEL	Hole and crosspiece for lateral fixing	For the fixing of containers to each other or to a wall.		
IOP-FR*	Raised base	Allows a reduction in the volume and weight of the soil when plants do not require the whole		* € 20 - 60 Excl. tax acc. to size of container
IOP-PSE **	Useful height reduced by an expanded polystyrene filling	capacity - Height adjustable to your needs.	** If installed on casters, feet, pads ** or requiring a bottom on a low level.	** cost acc. to container size and height to fill
IOP-ARD	Edges and rounded corners	Replaces edges and chamfered angles used in standard design.	Ideal for use in nurseries or schools to prevent the risk of injury.	€ 20 Excl.tax /per container